

Edmonton

13504 St. Albert Trail
Edmonton, AB T5L 4P4
Phone: 780.453.3761
Fax: 780.454.1584
Toll Free: 1.800.463.3667

Vancouver

19733 96 Avenue
Langley, BC V1M 3C9
Phone: 604.888.2550
Fax: 604.888.6133
Toll Free: 1.800.361.3667

Kelowna

#200, 144 Cambro Road
Kelowna, BC V1X 7T3
Phone: 250.765.4765
Fax: 250.765.3747
Toll Free: 1.800.880.0755

Calgary

#5, 3201 Ogden Road SE
Calgary, AB T2G 4N4
Phone: 403.255.3300
Fax: 403.253.8025
Toll Free: 1.800.561.9871

Toronto

6555 Kestrel Road
Mississauga, ON L5T 1P4
Phone: 905.564.3522
Fax: 905.564.3527
Toll Free: 1.800.465.7091



www.steel-craft.ca

Style.
Beauty.
Efficiency.

CarriageCraft
SERIES



www.steel-craft.ca

Features & Benefits



R-Value

CC-10: 1- 1/8" Thick - An Insulation R-Value of 10.40
CC-16: 1-3/4" Thick – An Insulation R-Value of 16.04

Offers twice the insulating value of a door with common polystyrene insulation. Polyurethane boasts important advantages over polystyrene. Its high density composition delivers higher R-value per inch of thickness. Polyurethane offers great resistance to moisture reducing the risk of mold or mildew. It also possesses dimensional stability and will not soften or melt, remaining strong even at elevated temperatures.

Premium quality in every layer

We use the finest quality Canadian galvanized steel finished with primer and exterior polyester paint top coats. The paint acts as a barrier protecting the underlying zinc coating. The finished product delivers unmatched quality and extends the life of your garage door.

A Thermal-Break separates the outside and inside steel skins to reduce cold/heat conductivity and stops frost and moisture from collecting on the inside of the door.

Hardware

We design and manufacture all hardware components to ensure optimum strength, durability and smooth operation of the complete door system. Our hardware is amongst the highest gauge and strongest steel in the market.

Only heavy duty hardware with top quality nylon rollers are used to ensure long life and smooth quiet operation. Computer balanced oil tempered torsion springs, steel bearings and die cast cable drums are used for ease of operation. Corrosion resistant galvanizing is used on all steel parts to reduce the possibility of rusting.

Weather-Stripping

Exterior grade double finned perimeter steel/vinyl weather-stripping provides excellent protection from outside elements as well as a crisp finishing touch to the perimeter of your door.

Weather Seal in Between Sections and on Floor

Air and wind infiltration is eliminated by the use of a continuous weather seal inserted between each section. Arctic grade vinyl bulb-shaped floor seal conforms to minor floor irregularities providing protection against penetration of outside air, dust, dirt and moisture.

Virtually Maintenance Free

Finished with a factory applied, baked-on, two-coat exterior polyester paint finish on both sides giving years of maintenance free operation. The continuous seamless steel inside skin brightens the interior of the garage and is easy to keep clean.

CFC and HCFC Free Polyurethane Core

Provides superior strength, excellent energy efficiency and is highly dent resistant due to the high tensile steel backed by rigid polyurethane foam.

Warranty

The complete door is covered by a warranty against workmanship and material plus a 15 year warranty against cracking, splitting or deterioration due to rust. Seven years against delamination of the polyurethane foam from the steel skin on the panel and one year on defects in workmanship and material. See dealer for complete warranty details.

Door Colours

Carriage-house panel design with wood grain finish. Painted inside and out, the continuous seamless steel inside skin brightens the interior of the garage and is easy to keep clean. The door may also be painted to suit the exterior colour specifications of your home.

White



Sandstone



Brown



Linen - NEW!



Note: The accuracy of the colours displayed may not be true. To obtain an exact colour reference, please contact a Steel-Craft dealer for colour samples.

Window Designs

We use premium quality glass for all our window applications.

Window Size: 38" x 14"

Window Frame & Snap-In Decorative Design Colours: White, Sandstone, Brown, Linen-NEW!

Plain Lite

Available in 1/8" Single Pane and 5/8" ThermoPane



Snap-In Decorative Designs

Available in Single Pane and ThermoPane



Cascade



Waterton



Stockton



Stockbridge



Somerton



Wynbridge

Hinges & Handles



Sicillian Hinge



Milano Forged Black Iron Lift Handle



Tuscan Hinge



Veneto Stamped Steel Handle for Vintage Door



Umbria Hinge



San Marino Lift Handle

Door Size

CC-10: Available in standard heights of 6' thru 10' with a maximum width of 16'

CC-16: Available in standard heights of 6' thru 28' with a maximum width of 18'

Headroom: Standard Headroom requirements of 12", however, low headroom kits are available for special applications